

SINOTRUK



HOWO-TX EV

6x4 TRACTOR (RHD)

HOWO-TX EV 6x4 TRACTOR (RHD)

Model	ZZ4257Y384GZ1RB(S)EV6A
Gross Vehicle Weight	90,000kg
Chassis Overall Dimensions (L×W×H)(mm)	7550x2550x3700
Wheelbase (mm)	3800+1415
Front Overhang(mm)	1500
Rear Overhang (mm)	835
Drive type	6×4
Cab	HOWO-TX-M Cab, Automatic Single Refrigeration A/C, Manual Cab Tilting, Automatic Lifting Window, Four-point Hydraulic Suspension Cab, Two-Level Stepping Board, Hydraulic Suspension Driver Seat
Driving Motor Type	HOWO - TZ388XS-ZQV13 - Central Drive
Rated Power(kW)/Rotation Speed (r/min) /Torque(N.m)	340/2100/1500
Peak Power(kW)/Rotation Speed (r/min) /Torque(N.m)	520/3500/3000
Transmission Type	HW30706XAL
Number of Gears	6 forward gears, 1 reverse gears
gear ratio	Forward 11.765/7.09/4.318/2.725/1.641/1, Reverse11.765
Power Take Off	HW70
Chassis Frame	Triple-layer frame (8+8+8/318)
Front Axle	VGD95 (drum-type)
Rear Axle	MCP23ZG double axles (i=6.73)
Suspension	Front and rear strengthened leaf spring (11/11/14)
Brake	Automatic brake adjustment, ABS
Battery Capacity(kwh)	400/600
Energy Supply Method	Double- Gun DC Charging / 5min swapping
Charging Standard	Chinaese/European Standard
Charging Time	20% - 80% < 50min
Tyre	12.00R24
Protections	Metal Bumper
Fifth wheel	JOST 3.5 inch

The manufacture reserves the right of technical alteration/change for better improvement without prior notice.