

SINOTRUK



HOWO-V7X

8x4 ELECTRIC DUMPER (RHD)

HOWO-V7X EV 8x4 DUMPER (RHD)

Model	ZZ3312V5267Z1B(S)EVR
Gross Vehicle Weight(kg)	70,000
Overall Dimensions (LxWxH)(mm)	12100x2800x4300
Wheelbase (mm)	1950+5170+1415
Front Overhang(mm)	1500
Rear Overhang (mm)	2150
Battery Back To End (mm)	7700
Drive Type	8x4
Cab	V7-X, Single Refrigeration A/C, Manual Cab Tilting, Automatic Lifting Window, Four-point Hydraulic Suspension Cab, Two-Level Stepping Board, Air Suspension Driver Seat
Driving Motor Type	HOWO - TZ388XSCDW18 - Central Drive
Rated Power(kW)/Rotation Speed (r/min)/ Torque (N.m)	375/1800/2000
Peak Power(kW)/Rotation Speed (r/min)/ Torque (N.m)	575/3500/3060
Transmission Type	TS-0425C
Number of Gears	4 forward gears, 1 reverse gear
Gear Ratio	Forward: 8.51/4.33/2.31/1.00 , Reverse: 8.51
Power Take Off	HJ700A
Chassis Frame	Triple-layer frame (8+8+8/318)
Front Axle(T)	Rated payload: 9.5 double axles (drum brake)
Rear Axle(T)	Rated payload: 56 double drive axles (drum brake, i=6.73,optional: 5.92)
Suspension	Front and rear strengthened leaf spring (11/11/14)
Brake	Automatic brake adjustment, ABS
Battery Capacity(kwh)	400/600
Energy Supply Method	Triple - Gun DC Charging / 5min swapping
Charging Standard	Chinese/European Standard
Charging Time	20% - 80% < 50min
Tyre	12.00R24/12.00R20
Protection	Metal Bumper
Cargo Bucket(m³)	51

The manufacture reserves the right of technical alteration/change for better improvement without prior notice.